

Series 1-100 - Mobile examination lamp with joint-arm, on a fixed height stand

L111131A

PRODUKTBESCHREIBUNG

| | |
|--------------------------|--|
| Types of arm | Joint arm with spring balance joint |
| For attachment to | Pole with roller base |
| Working radius | 800 mm |
| Colour of lamp | White |
| Joint pin | Ø 18, L 35 mm |
| Light source | LED, 9W |
| Light output | > 70.000 lx / 500 mm; 20.000 lx / 1000 mm |
| Luminous flux (lm) | 550 lm |
| Light field diameter D10 | ~ 130 / 250 mm at 500 / 1.000 mm |
| Light colour | ~ 4000 ± 200 K |
| Colour rendering index | > Typ 90 Ra |
| Life expectancy | > 50,000 h (light source) |
| Electrical mains | 100 - 240 V, 50 - 60 Hz |
| Power switch | Integrated in the transformer housing |
| Motion control | Turn on/ off, Dimming |
| Castor base | steel, white coated |
| Base diameter | Ø 635 mm |
| Castors | Twin castors |
| Note | Due to measurement and production given data may deviate by approx. -10% to + 20%. |



VERPACKUNGSEINHEIT: UNIT

| | |
|--------------|---------|
| Breite Box1 | 0,2 m |
| Höhe Box1 | 0,33 m |
| Länge Box1 | 1,2 m |
| Gewicht Box1 | 10,5 kg |



Optimal illuminance
with dimming function



Touchless
Motion control



L111131A

Series 1-100 - Mobile examination lamp



Anwendung

lighthead can easily be
rotated and pivoted

very easy and fast assembly
through a plug in and out
system with only 1 screw
connection