IV stand / Drip stand
Material: Stainless steel

I-H31121

PRODUCT DESCRIPTION

Field of application	Homecare
Material	Stainless steel
Colour of plastic parts	Grey
Bottle Holder	Plastic
Number of hooks	4
Arrangement of the hooks	90° to each other
Type of height adjustment	Screw height adjustment
Maximum length/height	2.150 mm
Minimum length/height	1.350 mm
Inner tube diameter	Ø 18 mm
Outer tube diameter	Ø 25 mm
Base diameter	Ø 635 mm
Castors	Twin castors
Castor diameter	Ø 50 mm
Number of castors	5; 2 with brakes and elect. conductivity
Drip vessel sterilizable	Yes
Total load capacity (kg)	8
Load capacity per system (kg)	8
Load capacity per hook (kg)	2

PACKAGING UNIT: PAIR

Width Box1	0,19 m
Height Box1	0,10 m
Length Box1	1,19 m
Weight Box1	6,50 kg

PACKAGING UNIT: UNIT

Width Box1	0,19 m
Height Box1	0,10 m
Length Box1	1,19 m
Weight Box1	3,50 kg

Shipping optimized packaging
up to 50 pieces on one pallet

Set-Up-Time
2 - 3 minutes

Made in Germany

© provita medical gmbh & co. kg – Technische Änderungen vorbehalten.

I-H31121

IV stand / Drip stand



Area of application

very easy and fast assembly through a plug in and out system with only 1 screw connection

comfortable height adjustment through a screw-height adjustment with an integrated, surface-gently mold clamping element

Technology

All plastic parts are lightfast

castors with non-marking tread

Stainless steel tubes according to DIN EN 10217-7

Material ultrasonic and eddy current tested (according to EN 10246-9/3)

The integrated pull-out limiter prevents the adjustable tubes from separating

Safety bottle cross according to DIN ISO 15375

base made of plastic with two conductive base legs

a sealing cap prevents the IV-pole from hygienical senstive liquids

Safety

Low risk of pinching when retracting and extending the IV-pole thanks to the built-in safety distance

No risk of injury thanks to the rounded shape of the bottle hooks

The geometry of the hooks prevents the infusion bottle from falling out

Made in Germany

© provita medical gmbh & co. kg – Technische Änderungen vorbehalten.