

IV stand / Drip stand

Material: Aluminium

I-H81121

PRODUCT DESCRIPTION

| | |
|-------------------------------|--|
| Field of application | Homecare |
| Material | Aluminium |
| Colour of plastic parts | Black |
| Bottle Holder | Plastic |
| Number of hooks | 4 |
| Arrangement of the hooks | 90° to each other |
| Type of height adjustment | Screw height adjustment |
| Maximum length/height | 2,150 |
| Minimum length/height | 1,350 |
| Inner tube diameter | Ø 18 mm |
| Outer tube diameter | Ø 25 mm |
| Base diameter | Ø 635 mm |
| Castors | Twin castors |
| Castor diameter | Ø 50 mm |
| Number of castors | 5; 2 with brakes and elect. conductivity |
| Drip vessel sterilizable | Yes |
| Total load capacity (kg) | 8 |
| Load capacity per system (kg) | 8 |
| Load capacity per hook (kg) | 2 |



PACKAGING UNIT: PAIR

| | |
|-------------|--------|
| Width Box1 | 0,19 m |
| Height Box1 | 0,1 m |
| Length Box1 | 1,19 m |
| Weight Box1 | 6,5 kg |

PACKAGING UNIT: UNIT

| | |
|-------------|--------|
| Width Box1 | 0,19 m |
| Height Box1 | 0,1 m |
| Length Box1 | 1,19 m |
| Weight Box1 | 3,5 kg |



Shipping optimized packaging
up to 50 pieces on one pallet



Set-Up-Time
2 - 3 minutes



I-H81121

IV stand / Drip stand



Area of application

very easy and fast assembly through a plug in and out system with only 1 screw connection

comfortable height adjustment through a screw-height adjustment with an integrated, surface-gently mold clamping element



Technology

All plastic parts are lightfast

castors with non-marking tread

The integrated pull-out limiter prevents the adjustable tubes from separating

Safety bottle cross according to DIN ISO 15375

base made of plastic with two conductive base legs

a sealing cap prevents the IV-pole from hygienical sensitive liquids



Safety

Low risk of pinching when retracting and extending the IV-pole thanks to the built-in safety distance

No risk of injury thanks to the rounded shape of the bottle hooks

The geometry of the hooks prevents the infusion bottle from falling out

