

IV-Stand Low Gravity

8 Hooks

I-LOW015

PRODUCT DESCRIPTION

Field of application	Intensive Care
Material	Stainless steel / Plastic
Colour of plastic parts	Blue / Black
Number of hooks	8
Arrangement of the hooks	90° to each other
Type of height adjustment	Stainless steel screw height adjustment
Maximum length/height	2.270 mm
Minimum length/height	1.420 mm
Inner tube diameter	Ø 25 mm
Outer tube diameter	Ø 33,7 mm
Length of outer tube	1.200 mm
Base leg profile	Ø 33,7 mm
Base weight	Weighted
Base diameter	Ø 680 mm
Castors	Apparatus castors
Castor diameter	Ø 75 mm
Number of castors	5 with brakes and elect. conductivity
Total load capacity (kg)	13
Load capacity per system (kg)	8
Load capacity per hook (kg)	2



PACKAGING UNIT: UNIT

Width Box1	0,21 m
Height Box1	0,13 m
Length Box1	1,46 m
Weight Box1	12,50 kg



IV-Stand Low Gravity



Area of application

The outer tube offers enough space to attach various devices at a user-friendly operating height



Technology

All plastic parts are lightfast

Stainless steel tubes according to DIN EN 10217-7

Material ultrasonic and eddy current tested (according to EN 10246-9/3)

The integrated pull-out limiter prevents the adjustable tubes from separating

Safety bottle cross according to DIN ISO 15375

Increased resistance to corrosion thanks to the base made of glass-fibre reinforced plastic



Economy

Compact packaging allows for low-cost shipping



Safety

The base legs are sealed with plastic plugs (no risk of injury)

Low risk of pinching when retracting and extending the IV-pole thanks to the built-in safety distance

The Softdrop system dampens and controls the lowering of the inner tube

No risk of injury thanks to the rounded shape of the bottle hooks

The geometry of the hooks prevents the infusion bottle from falling out

