

MRI - I.V. Stand / Drip Stand for devices up to 3 Tesla

I-M91121

PRODUCT DESCRIPTION

Field of application	MRI
Material	Aluminium
Colour of plastic parts	Darkgrey
Bottle Holder	Plastic
Number of hooks	4
Arrangement of the hooks	90° to each other
Type of height adjustment	Screw height adjustment
Maximum length/height	2.090 mm
Minimum length/height	1,250
Inner tube diameter	Ø 18 mm
Outer tube diameter	Ø 25 mm
Length of outer tube	500 mm
Base diameter	Ø 635 mm
Castors	Twin castors
Castor diameter	Ø 50 mm
Number of castors	5 with brakes, without elect. conductivity
Drip vessel sterilizable	Yes
Total load capacity (kg)	8
Load capacity per system (kg)	8
Load capacity per hook (kg)	2



PACKAGING UNIT: UNIT

Width Box1	0,19 m
Height Box1	0,1 m
Length Box1	1,19 m
Weight Box1	3,8 kg



MR conditional



Set-Up-Time
2 - 3 minutes





Area of application

comfortable height adjustment through a screw-height adjustment with an integrated, surface-gently mold clamping element



Technology

All plastic parts are lightweight

castors with non-marking tread

The integrated pull-out limiter prevents the adjustable tubes from separating

Safety bottle cross according to DIN ISO 15375

base made of plastic with two conductive base legs

suitable for the use in areas with a magnetic flux density of up to 3,0 tesla

with a report over a magnetic resonance test (available on request)

a sealing cap prevents the IV-pole from hygienical sensitive liquids



Safety

Low risk of pinching when retracting and extending the IV-pole thanks to the built-in safety distance

No risk of injury thanks to the rounded shape of the bottle hooks

The geometry of the hooks prevents the infusion bottle from falling out