IV Stand Normal care Material: chromed steel



I-N42122

PRODUCT DESCRIPTION

Field of application	Normal Care
Material	Chromed steel
Colour of plastic parts	Blue
Bottle Holder	Chromed steel to screw in, bottle holder
Number of hooks	4
Arrangement of the hooks	90° to each other
Type of height adjustment	Screw height adjustment
Maximum length/height	2,150
Minimum length/height	1,350
Inner tube diameter	Ø 18 mm
Outer tube diameter	Ø 25 mm
Length of outer tube	1,000
Base leg profile	25 x 25
Base weight	Unweighted
Base diameter	Ø 635 mm
Castors	Mono castors
Castor diameter	Ø 80 mm
Number of castors	5; 2 with brakes and elect. conductivity
Drip vessel sterilizable	Yes
Total load capacity (kg)	9.5
Load capacity per system (kg)	8
Load capacity per hook (kg)	2

PACKAGING UNIT: PAIR

Width Box1	0,19 m
Height Box1	0,1 m
Length Box1	1,19 m
Weight Box1	7,6 kg

PACKAGING UNIT: UNIT

Width Box1	0,19 m
Height Box1	0,1 m
Length Box1	1,19 m
Weight Box1	4,1 kg



High-gloss chrome-plated 3-layer-system

many o

many different configurations





I-N42122 IV Stand Normal care











Area of application

optimal hygienic characteristics (wipe disinfection)

very easy and fast assembly through a plug in and out system with only 1 screw connection

comfortable height adjustment through a screwheight adjustment with an integrated, surface-gently mold clamping element



Technology

All plastic parts are lightfast

The integrated pull-out limiter prevents the adjustable tubes from separating

Safety bottle cross according to DIN ISO 15375

great running characteristic through high value 80 mm Mono castors

a sealing cap prevents the IV-pole from hygienical senstive liquids



Economy

Compact packaging allows for low-cost shipping



Safety

The base legs are sealed with plastic plugs (no risk of injury)

Low risk of pinching when retracting and extending the IV-pole thanks to the built-in safety distance

No risk of injury thanks to the rounded shape of the bottle hooks

The geometry of the hooks prevents the infusion bottle from falling out

