

IV-stand / Drip stand

screw height adjustment

I-O11122

PRODUCT DESCRIPTION

Field of application	OR (initiation / recovery room)
Material	Stainless steel
Colour of plastic parts	Blue
Bottle Holder	Stainless steel to screw in, bottle holder
Number of hooks	4
Arrangement of the hooks	90° to each other
Type of height adjustment	Screw height adjustment
Maximum length/height	2,150
Minimum length/height	1,350
Inner tube diameter	Ø 18 mm
Outer tube diameter	Ø 25 mm
Length of outer tube	1,000
Base leg profile	30 x 15
Base weight	Unweighted
Base diameter	Ø 635 mm
Castors	Twin castors
Castor diameter	Ø 50 mm
Drip vessel sterilizable	Yes
Total load capacity (kg)	9.5
Load capacity per system (kg)	8
Load capacity per hook (kg)	2



PACKAGING UNIT: UNIT

Width Box1	0,73 m
Height Box1	0,18 m
Length Box1	0,67 m
Weight Box1	2,3 kg
Width Box2	0,19 m
Height Box2	0,1 m
Length Box2	1,19 m
Weight Box2	2,2 kg



Best hygienic properties
stainless steel (1.4301)



Seamless base construction
Electro-polished surface





Area of application

comfortable height adjustment through a screw-height adjustment with an integrated, surface-gently mold clamping element



Technology

All plastic parts are lightweight

castors with non-marking tread

Stainless steel tubes according to DIN EN 10217-7

Material ultrasonic and eddy current tested (according to EN 10246-9/3)

The integrated pull-out limiter prevents the adjustable tubes from separating

Safety bottle cross according to DIN ISO 15375

Welded stainless steel castor pins reduce the risk of rusting and improve the mechanical and hygienic conditions

a sealing cap prevents the IV-pole from hygienic sensitive liquids



Safety

The base legs are sealed with plastic plugs (no risk of injury)

Low risk of pinching when retracting and extending the IV-pole thanks to the built-in safety distance

No risk of injury thanks to the rounded shape of the bottle hooks

The geometry of the hooks prevents the infusion bottle from falling out