OR IV-stand with base weight
screw height adjustment



I-O23232

PRODUCT DESCRIPTION

Field of application	OR (initiation / recovery room)
Material	Stainless steel
Colour of plastic parts	Blue
Number of hooks	4
Arrangement of the hooks	90° to each other
Type of height adjustment	Stainless steel screw safety height adjustment, with softdrop
Maximum length/height	2.250 mm
Minimum length/height	1.500 mm
Inner tube diameter	Ø 25 mm
Outer tube diameter	Ø 33,7 mm
Length of outer tube	1.200 mm
Base leg profile	45 x 25 mm
Base diameter	Ø 635 mm
Castors	Twin castors
Castor diameter	Ø 75 mm
Number of castors	5 with brakes and elect. conductivity
Total load capacity (kg)	30
Load capacity per system (kg)	8
Load capacity per hook (kg)	2

PACKAGING UNIT: UNIT

Width Box1	0,58 m
Height Box1	0,20 m
Length Box1	0,62 m
Weight Box1	11,40 kg
Width Box2	0,22 m
Height Box2	0,14 m
Length Box2	1,46 m
Weight Box2	3,80 kg

Made in Germany

© provita medical gmbh & co. kg – Technische Änderungen vorbehalten.

I-O23232

OR IV-stand with base weight

Area of application

comfortable height adjustment through a screw-height adjustment with an integrated, surface-gently mold clamping element

Technology

All plastic parts are lightfast

Stainless steel tubes according to DIN EN 10217-7

Material ultrasonic and eddy current tested (according to EN 10246-9/3)

The integrated pull-out limiter prevents the adjustable tubes from separating

Safety bottle cross according to DIN ISO 15375

a sealing cap prevents the IV-pole from hygienical senstive liquids

Safety

The base legs are sealed with plastic plugs (no risk of injury)

Low risk of pinching when retracting and extending the IV-pole thanks to the built-in safety distance

No risk of injury thanks to the rounded shape of the bottle hooks

The geometry of the hooks prevents the infusion bottle from falling out

Made in Germany

© provita medical gmbh & co. kg – Technische Änderungen vorbehalten.