

IV Stand Premium Care

Pump carrier with curved base legs

I-PRE100

PRODUCT DESCRIPTION

Field of application	Intensive Care
Material	Stainless steel/ Aluminium
Color	Blue
Colour of plastic parts	Black
Bottle Holder	Stainless steel, bottle bar
Number of hooks	4
Arrangement of the hooks	In line with each other
Type of height adjustment	Stainless steel screw height adjustment
Maximum length/height	2,100
Minimum length/height	1,835
Inner tube diameter	Ø 25 mm
Outer tube diameter	Ø 33,7 mm
Length of outer tube	1,500
Base leg profile	Ø 33,7 mm
Base weight	Weighted
Base diameter	660 / 844 mm
Castors	Apparatus castors
Castor diameter	Ø 75 mm
Number of castors	5 with brakes and elect. conductivity
Total load capacity (kg)	45
Load capacity per system (kg)	8
Load capacity per hook (kg)	2



PACKAGING UNIT: UNIT



Extremely high resilience



Softdrop system
for maximum security





Area of application

optimal hygienic characteristics (wipe disinfection)

The outer tube offers enough space to attach various devices at a user-friendly operating height



Technology

All plastic parts are lightweight

Stainless steel tubes according to DIN EN 10217-7

Material ultrasonic and eddy current tested (according to EN 10246-9/3)

The integrated pull-out limiter prevents the adjustable tubes from separating

Safety bottle cross according to DIN ISO 15375

Welded stainless steel castor pins reduce the risk of rusting and improve the mechanical and hygienic conditions

Reinforced bottle holder allows hanging 5 liters of rinsing solutions

made from high-quality stainless steel



Safety

The base legs are sealed with plastic plugs (no risk of injury)

Low risk of pinching when retracting and extending the IV-pole thanks to the built-in safety distance

Cylindrical and polished base legs reduce the surface area for dirt and germs to settle

The Softdrop system dampens and controls the lowering of the inner tube

No risk of injury thanks to the rounded shape of the bottle hooks

The geometry of the hooks prevents the infusion bottle from falling out