

Mobile Transfer Cart » provi-Dock «

Size » M «

IDOCK510

PRODUCT DESCRIPTION

Material	Stainless steel
Integrated, variable spacers	0 - 60 mm [Standard] - up to 170 mm as optional accessory
Bottle Holder	Stainless steel, for screw-in
Number of hooks	3
Arrangement of the hooks	120° to each other
Load capacity (kg)	50 kg
Type of height adjustment	One-hand height adjustment
Maximum length/height	1,940
Minimum length/height	1,770
Extends the bed by	appr. 415
Medical rails	4 pcs. each 25 x 10 x 680
Tube version	1 tube, 1 IV-Pole
Round tubes length	1.350 mm
Round tubes diameter (mm)	Ø 38 mm
Round tubes wall thickness (mm)	2 mm
Distance round tube - IV-Pole	500 mm
Size of base plate (mm)	appr. 510 x 600
Castors	Twin castors
Castor diameter	Ø 125 mm
Bed mounting	Height adjustable docking bar with 2 docking hooks
Docking bar	standard
Grounding	through grounding ring
Total load capacity (kg)	50
Load capacity per system (kg)	6
Load capacity per hook (kg)	2



PACKAGING UNIT: UNIT



IDOCK510

Mobile Transfer Cart » provi-Dock «

