

Series 1-100 - Mobile examination lamp with gooseneck arm, on a fixed Height Stand

L111111A

PRODUCT DESCRIPTION

| | |
|--------------------------|------------------------------------------------------------------------------------|
| Types of arm | Gooseneck arm |
| For attachment to | Pole with roller base |
| Working radius | 800 mm |
| Colour of lamp | White |
| Joint pin | Ø 18, L 35 mm |
| Light source | LED, 9W |
| Light output | > 70.000 lx / 500 mm; 20.000 lx / 1000 mm |
| Luminous flux (lm) | 550 lm |
| Light field diameter D10 | ~ 130 / 250 mm at 500 / 1.000 mm |
| Light colour | ~ 4000 ± 200 K |
| Colour rendering index | > Typ 90 Ra |
| Life expectancy | > 50,000 h (light source) |
| Electrical mains | 100 - 240 V, 50 - 60 Hz |
| Power switch | Integrated in the transformer housing |
| Note | Due to measurement and production given data may deviate by approx. -10% to + 20%. |

PACKAGING UNIT: UNIT

| | |
|-------------|---------|
| Width Box1 | 0,2 m |
| Height Box1 | 0,33 m |
| Length Box1 | 1,2 m |
| Weight Box1 | 10,5 kg |



Optimal illuminance
with dimming function



Touchless
Motion control



L111111A

Series 1-100 - Mobile examination lamp



Economy

high life expectancy of the
light source

low maintenance effort



Safety

protected interior cable
management

The base legs are sealed
with plastic plugs (no risk of
injury)

electrically conductive

