

Series 1-100 - Mobile examination lamp

double-joint arm, fixed height stand

L111181A

PRODUCT DESCRIPTION

Types of arm	Double joint arm with spring balance joint
For attachment to	Pole with roller base
Working radius	1100 mm
Colour of lamp	White
Joint pin	Ø 18, L 35 mm
Light source	LED, 9W
Light output	> 70.000 lx / 500 mm; 20.000 lx / 1000 mm
Luminous flux (lm)	550 lm
Light field diameter D10	~ 130 / 250 mm at 500 / 1.000 mm
Light colour	~ 4000 ± 200 K
Colour rendering index	> Typ 90 Ra
Life expectancy	> 50,000 h (light source)
Electrical mains	100 - 240 V, 50 - 60 Hz
Power switch	Integrated in the transformer housing
Motion control	Turn on/ off, Dimming
Castor base	steel, white coated
Base diameter	Ø 635 mm
Castors	Twin castors
Note	Due to measurement and production given data may deviate by approx. -10% to +20%.



PACKAGING UNIT: UNIT

Width Box1	0,2 m
Height Box1	0,33 m
Length Box1	1,2 m
Weight Box1	10,5 kg



Optimal illuminance
with dimming function



Touchless
Motion control



L111181A

Series 1-100 - Mobile examination lamp



Area of application

lighthead can easily be rotated and pivoted

very easy and fast assembly through a plug in and out system with only 1 screw connection