

LED - Lamp with double-joint articulated arm **provita[®]** with spring-balance technology medical

L210215A

PRODUCT DESCRIPTION

| | |
|--------------------------|---|
| Types of arm | Double joint arm with spring balance joint |
| Colour of lamp | White |
| Joint pin | Ø 18, L 35 mm |
| Light source | LED, 8W |
| Light output | approx. 23.300 Lux / 500 mm |
| Light field diameter D10 | 220 / 425 at 500 / 1,000 |
| Light colour | approx. 4,300 K |
| Life expectancy | up to 67,000 h (light source) |
| Electrical mains | 220 V, 50 - 60 Hz |
| Power switch | Integrated in the transformer housing |
| Working radius | about 1.100 |
| Optional | dimmer on request / international plug / 110 V / colour correction filter |



PACKAGING UNIT: UNIT

| | |
|-------------|--------|
| Width Box1 | 0,22 m |
| Height Box1 | 0,18 m |
| Length Box1 | 0,69 m |
| Weight Box1 | 3,4 kg |



Impact resistant housing
best and sturdy plastic properties



Spring support
for better usability



L210215A

LED - Lamp with double-joint articulated arm



Area of application

optimal hygienic characteristics (wipe disinfection)



Economy

high life expectancy of the light source

low maintenance effort



Safety

protected interior cable management

lighthead with hardened / scratch-proofed safety glass

