

Series 2 - Mobile examination lamp with double-joint articulated arm

L210226A

PRODUCT DESCRIPTION

Types of arm	Double joint arm
For attachment to	Pole with roller base
Colour of lamp	White
Joint pin	Ø 18, L 35 mm
Light source	LED, 8W
Light output	approx. 23.300 Lux / 500 mm
Light field diameter D10	220 / 425 at 500 / 1,000
Light colour	approx. 4,300 K
Life expectancy	up to 67,000 h (light source)
Electrical mains	220 V, 50 - 60 Hz
Power switch	Integrated in the transformer housing
Working radius	? 800 mm
Tube height	approx. 1.070
Castor base	steel, white coated
Base diameter	Ø 635 mm
Castors	Twin castors
Installation on	Mobile stand fixed height
Optional	Dimmer on request / international plug / 110 V version

PACKAGING UNIT: UNIT



Perfectly focused lighting
clearly defined light field



Energy efficient
modern and economical LED technology



L210226A

Series 2 - Mobile examination lamp



Area of application

optimal hygienic characteristics (wipe disinfection)

very easy and fast assembly through a plug in and out system with only 1 screw connection



Economy

high life expectancy of the light source

low maintenance effort



Safety

protected interior cable management

lighthead with hardened / scratch-proofed safety glass

The base legs are sealed with plastic plugs (no risk of injury)

electrically conductive

