Series 2 - Mobile examination lamp
with flexible arm

L220236A

PRODUCT DESCRIPTION

Types of arm	Gooseneck arm
For attachement to	Height-adjustable stand with roller base
Colour of lamp	White
Joint pin	Ø 18, L 35 mm
Light source	LED, 8W
Light output	approx. 23.300 Lux / 500 mm
Light field diameter D10	220 / 425 at 500 / 1,000
Light colour	approx. 4,300 K
Life expectancy	up to 67,000 h (light source)
Electrical mains	220 V, 50 - 60 Hz
Power switch	Integrated in the transformer housing
Working radius	? 800 mm
Castor base	steel, white coated
Base diameter	Ø 635 mm
Castors	Twin castors
Installation on	mobile stand height adjustable
Optional	Dimmer on request / international plug / 110 V version

PACKAGING UNIT: UNIT

Width Box1	0,19 m
Height Box1	0,22 m
Length Box1	1,03 m
Weight Box1	12,80 kg

Made in Germany

© provita medical gmbh & co. kg – Technische Änderungen vorbehalten.

L220236A

Series 2 - Mobile examination lamp

Area of application

optimal hygienic characteristics (wipe disinfection)

very easy and fast assembly through a plug in and out system with only 1 screw connection

Economy

high life expectancy of the light source

low maintenance effort

Safety

protected interior cable management

lighthead with hardened / scratch-proofed safety glas

The base legs are sealed with plastic plugs (no risk of injury)

Low risk of pinching when retracting and extending the IV-pole thanks to the built-in safety distance

electrically conductive

Made in Germany

© provita medical gmbh & co. kg – Technische Änderungen vorbehalten.