

Reading Lamp, LED

with flexible arm and cord switch

L320214S

PRODUCT DESCRIPTION

| | |
|------------------------|---|
| Types of arm | Gooseneck arm |
| Colour of lamp | Silver |
| Joint pin | Ø 18, L 35 mm |
| Light source | LED, 6W |
| Light output | 700 Lux / 500 mm |
| Luminous flux (lm) | 470 lm |
| Light colour | 2,700 K |
| Colour rendering index | Type 80 |
| Life expectancy | approx. 30,000 h (light source) |
| Electrical mains | 220 - 240 V, 50 - 60 Hz |
| Power switch | with cord switch |
| Working radius | approx. 600 mm |
| Operating mode | continuous use |
| Optional | double joint articulated arm / international plug |



PACKAGING UNIT: UNIT

| | |
|-------------|---------|
| Width Box1 | 0,23 m |
| Height Box1 | 0,18 m |
| Length Box1 | 1,01 m |
| Weight Box1 | 1,75 kg |



Best hygienic properties
smooth surface, small gaps and joints



Energy efficient
modern and economical LED technology



L320214S

Reading Lamp, LED



Area of application

optimal hygienic characteristics (wipe disinfection)



Economy

high life expectancy of the light source

low maintenance effort

