

# LED - Reading Lamp with flexible arm

## short version

**L400069S**

### PRODUCT DESCRIPTION

Colour of lamp	Silver
Joint pin	Ø 18, L 35 mm
Light source	LED 12 V / 3 W, 36°
Light output	1,480 lux / 500 mm
Luminous flux (lm)	230 lm
Light colour	4,000 K
Colour rendering index	Type 80
Life expectancy	25,000 h (light source)
Electrical mains	100 - 240 V, 50 - 60 Hz
Power switch	at the lamp head
Working radius	approx. 600 mm
Orientating light	Integrated in switch
Transformer	plug transformer
Total length	approx. 830 mm
Operating mode	continuous use
Optional	With international plug, with wide range power supply (without orientation light) / with cord switch



### PACKAGING UNIT: UNIT

Width Box1	0,18 m
Height Box1	0,11 m
Length Box1	0,95 m
Weight Box1	1,7 kg



**Best hygienic properties**  
smooth surface, small gaps and joints



**Energy efficient**  
modern and economical LED technology



L400069S

## LED - Reading Lamp with flexible arm



### Area of application

optimal hygienic characteristics (wipe disinfection)

On / off switch with night orientation light integrated in luminaire head



### Economy

high life expectancy of the light source

low maintenance effort

