

Series 5 - Mobile examination lamp with switch and OSRAM LED

L511130A

PRODUCT DESCRIPTION

For attachment to	Pole with roller base
Colour of lamp	White
Light source	24 V / 27 W
Light output	60,000 lux / 1,000 mm
Luminous flux (lm)	720 lm
Light field diameter D10	approx. 170 at 1,000
Light colour	approx. 4,500 K
Colour rendering index	Type 94
Life expectancy	> 50,000 h (light source)
Protection class	IP 20
Safety class	II
Electrical mains	AC 120 - 240 V, 50 - 60 Hz
Total power output	35 W
Red-colouring index R9	> 97
Skin rendering index R13	> 98
Luminous efficiency	31 lm / W
Electrical rating after	DIN VDE 0750 T1
Height adjustment	approx. 1,000
Swivel radius	approx. 950
Handle	sterilisable
Operating mode	continuous use

PACKAGING UNIT: UNIT

Width Box1	0,49 m
Height Box1	0,45 m
Length Box1	1,2 m
Weight Box1	11 kg
Width Box2	0,16 m
Height Box2	0,43 m
Length Box2	0,65 m
Weight Box2	8 kg



Perfectly focused lighting
clearly defined light field



L511130A

Series 5 - Mobile examination lamp

