Series 6: LED Tube Reading Lamp
with Flexarm, angled

L620025A

PRODUCT DESCRIPTION

total luminous flux	220 lm
Types of arm	Gooseneck arm bended
Colour of lamp	White
Light output	? 2.000 Lux / 500 mm
Luminous flux (lm)	53 lm/W at 100 mA
Light colour	5.000 K
Life expectancy	> 25.000 h
Electrical mains	AC 100 - 240 V, 50 - 60 Hz
Electrical load	2,1 W
Supply voltage of Lamp	12 V (DC)
Spigot diameter	18 mm
Angle of lamp head rotation	315°
Angle of reflected light	30°
Optional	international plug / link-up to bed controls / operated through bed controls by the patient

PACKAGING UNIT: UNIT

Width Box1	0,12 m
Height Box1	0,80 m
Length Box1	1,50 m
Weight Box1	1,50 kg

Made in Germany

© provita medical gmbh & co. kg – Technische Änderungen vorbehalten.

L620025A

Series 6: LED Tube Reading Lamp

Area of application

optimal hygienic characteristics (wipe disinfection)

Economy

high life expectancy of the light source

low maintenance effort

Safety

protected interior cable management

Made in Germany

© provita medical gmbh & co. kg – Technische Änderungen vorbehalten.