

# Series 6: LED Tube Reading Lamp with Flexarm, angled

L620025S

## PRODUCT DESCRIPTION

|                             |   |
|-----------------------------|---|
| total luminous flux         | 220 lm  |
| Types of arm                | Gooseneck arm bended  |
| Colour of lamp              | Silver  |
| Light output                | ? 2.000 Lux / 500 mm  |
| Luminous flux (lm)          | 53 lm/W at 100 mA   |
| Light colour                | 5.000 K   |
| Life expectancy             | 25,000 h (light source)   |
| Electrical mains            | AC 100 - 240 V, 50 - 60 Hz  |
| Electrical load             | 2,1 W   |
| Supply voltage of Lamp      | 12 V (DC)   |
| Spigot diameter             | 18 mm   |
| Angle of lamp head rotation | 315°  |
| Angle of reflected light    | 30°   |
| Optional                    | international plug / link-up to bed controls / operated through bed controls by the patient |



## PACKAGING UNIT: UNIT

|             |        |
|-------------|--------|
| Width Box1  | 0,12 m |
| Height Box1 | 0,08 m |
| Length Box1 | 1,5 m  |
| Weight Box1 | 1,5 kg |



Energy efficient  
modern and economical LED technology



Best hygienic properties  
smooth surface, small gaps and joints



L620025S

## Series 6: LED Tube Reading Lamp



### Area of application

optimal hygienic characteristics (wipe disinfection)



### Economy

high life expectancy of the light source

low maintenance effort



### Safety

protected interior cable management

