

Lamps

CATALOGUE

Examination lamps / Reading lamps

**Whether in the
examination room,
intensive care or at the
patient's bedside –**

**provita lamps
illuminate always
what is important:**

**the health
and well-being
of people.**

**The right choice for bright light
and glare-free illumination.**



The provita lamp series



efficient

flexible

glare-free

**We offer state-of-the-art solutions
for a variety of applications**



Series 1

Examination lamp LED
Touchless



Series 2

Small LED
examination/
reading lamp



Series 3

Reading lamp
with LED



Series 4

Small
LED
reading lamp



Series 5

Large
examination lamp
with LED central reflector



Series 6

Elegant
LED reading lamp



Accessories

For all
lighting systems

Series 1



The All-rounder examination lamp

The right choice for intensive light and glare-free illumination.



Motion Control



New LED - Module

LED Perfectly focused illumination

Light output >70.000 Lux / 500 mm

Light colour approx. 4.000 K \pm 200 K

Light field diameter D10
approx. 130 / 250 mm at 500 / 1.000mm

Electrical mains 100–240 V, 50–60 Hz

Simplified operation thanks to sensors:



Move HAND to turn ON / OFF



Hold HAND to DIM



To access the instructional video, simply scan the QR code

Series 1
Examination lamp

impact resistant
housing



modern
sensors



LED technology
Made in Germany

easy to
control



ideal
hygiene properties
(wipe disinfection)



Upon request: International plug / 110 V version
Many mounting options and further accessories starting on page 36.

Series 1
Basic version



**GOOSENECK
ARM LAMP**
Flexible positioning

Working radius approx. 800 mm
Total weight approx. 2.5 kg
Fixture pin Ø 18, L 35 mm

**DOUBLE-JOINT
ARM LAMP**
Large projection

Working radius approx. 1,100 mm
Total weight approx. 2.9 kg
Fixture pin Ø 18, L 35 mm

**JOINT
ARM LAMP**
Simple and safe

Working radius approx. 800 mm
Total weight approx. 2.6 kg
Fixture pin Ø 18, L 35 mm

With spring balance joint

LED L100081A

With spring balance joint

LED L100031A

Without spring balance joint

LED L100011A

Without spring balance joint

LED L100024A




For technical data
see provita.de



Precisely
adjustable

Series 1
Mobile lamps



Pole
(S000803A)
see accessories
p. 36



Stand
(S011820A)
see accessories
p. 36

**MOBILE LAMP
ON A FIXED-HEIGHT STAND**
**Steady and
secure**

Pole height with base approx. 1080 mm

Total weight approx. 7.8 kg

Fixture pin Ø 18, L 35 mm

Gooseneck arm

LED L111111A

**MOBILE LAMP
ON A HEIGHT-ADJUSTABLE STAND**
**Versatile and
height-adjustable**

Working radius approx. 800 mm

Total weight approx. 10.6 kg

Fixture pin Ø 18, L 35 mm

Gooseneck arm

LED L121111A

**Spring balance
double-joint arm**

LED L111181A

Double-joint arm

LED L121171A

**Spring balance
double-joint arm**

LED L121181A

Joint arm

LED L111124A

Spring balance joint arm

LED L111131A

Joint arm

LED L121124A

Spring balance joint arm

LED L121131A



CHILDREN LAMP
Bright colours
illuminate the stay

Working radius approx. 800 mm

Total weight approx. 7.8 kg

Fixture pin Ø 18, L 35 mm

LED L111120K



For more children infusion stands,
see INFUSION STAND catalogue and/or at provita.de



For technical data
see provita.de

Series 1
Wall and ceiling lamps



WALL MOUNTED LAMP
Space saving

Pivoting radius of lamp approx. 1,100 mm

Total weight approx. 3.2 kg

Angle of rotation approx. 330°

LED L140080A



Please order
cover separately

CEILING MOUNTED LAMP
Maximum ground clearance

Pivoting radius of lamp approx. 1,100 mm

Total weight approx. 6.7 kg / 7.2 kg / 7.7 kg

Angle of rotation approx. 370°

Length of ceiling stem 500 mm / 750 mm / 1,000 mm

For 2.5 m room height

LED L125080A

For 2.7 m room height


LED L127080A

For 3.0 m room height

LED L130080A

optional:
110 V version

Series 1
Ceiling lamps



**COVER
FOR CEILING LAMP**

Cover for Series 1

Diameter 320 mm

Z2K0679A

**SUBSTRUCTURE
FOR CEILING MOUNTING**

Also for suspended ceilings

With our substructure you have the possibility to connect our lamps of the series 1 & 5 to almost every ceiling. The type of fastening must be determined by the customer.

Our product consultants and technicians will be glad to assist you in clarifying all technical details.



+49 (0) 21 93 / 51 05 - 0



Please order ceiling mounting plates
& cover separately.



For technical data
see provita.de

Series 2



The decent examination & reading lamp

Compact solution
for variable use.



LED
Highly efficient &
perfectly focused

Light output > 23,300 Lux / 500 mm

Light colour approx. 4,000 K

Light field diameter D10 220 / 425 mm
at 500 / 1,000 mm

Electrical mains 90 – 260 V, 50 – 60 Hz

Series 2
Examination lamps & reading lamps



Upon request: Dimmer / international plug / 110 V version
Many mounting options and further accessories starting on page 36.



DOUBLE-JOINT ARM LAMP

Large projection

Projection of the lamp approx. 1,100 mm

Total weight approx. 2.45 kg

Fixture pin Ø 18, L 35 mm

GOOSENECK ARM LAMP

Flexible positioning

Projection of the lamp approx. 800 mm

Total weight approx. 2.2 kg

Fixture pin Ø 18, L 35 mm

With spring balance joint

LED L210215A


LED L220216A

Without spring balance joint*

LED L210216A



*With the spring balance joint, the lamps are positioned even more comfortably.



Pole
(S000803A)
see accessories
p. 36



Stand
(S011820A)
see accessories
p. 36

MOBILE LAMP ON A FIXED-HEIGHT STAND

**Versatile and
stable**

Projection of the lamp approx. 800 mm

Total weight approx. 7.5 kg

Fixture pin Ø 18, L 35 mm

Stand with gooseneck arm

LED L220226A

Stand with double-joint arm

LED L210226A

Stand with spring balance double-joint arm*

LED L210225A

MOBILE LAMP ON A HEIGHT-ADJUSTABLE STAND

**Flexible and
height adjustable**

Projection of the lamp approx. 800 mm

Total weight approx. 7.5 kg

Fixture pin Ø 18, L 35 mm

Stand with gooseneck arm

LED L220236A

Stand with double-joint arm

LED L210236A

Stand with spring balance double-joint arm*

LED L210235A

Fixed and height adjustable stand as singular item on page 36:



**For technical data
see provita.de**

Series 3



The practical reading lamp

Design & functionality,
perfectly connected.



LED
**Durable and low
energy consumption**

Light source LED, 7 W

Light output 520 Lux/500 mm

Light colour approx. 2,700 K

Luminous flux 803 lm

Electrical mains 220 – 240 V, 50 – 60 Hz

Series 3
Reading lamp



with night
orientation light



bulb is easy
to replace

ideal

hygiene properties
(wipe disinfection)



Made in
Germany

Upon request: international plug / 110 V version
Many mounting options and further accessories starting on page 36.

Series 3
Reading lamp



without external
room illumination



Series 3
Reading lamp



GOOSENECK ARM LAMP
Flexible positioning

Projection of the lamp

approx. 600 mm

Total weight approx. 1.25 kg

Fixture pin Ø 18, L 35 mm

LED

White L320114A

Silver L320114S

LED, with pull switch

White L320214A

Silver L320214S

optional:
International plug



For technical data
see provita.de

Series 4



The stylish reading lamp

Our best-seller
for comfortable reading.



LED
Long-live
High-Powered LED

Light source LED, 12 V / 3 W, 36°

Light output 1,870 Lux/500 mm

Light colour approx. 4,000 K

Luminous flux 230 lm

Electrical mains 100 – 240 V, 50 – 60 Hz

Series 4
Reading lamp



bulb is easy
to replace +



+ integrated
switch

ideal +
hygiene properties
(wipe disinfection)



Made in
Germany

Upon request: international plug / 110 V version
Many mounting options and further accessories starting on page 36.

Series 4
Reading lamp



GOOSENECK ARM LAMP
Flexible positioning

Projection of the lamp
approx. 600 mm

Switch at lamp head

Total length approx. 830¹ / 1,380² mm

Fixture pin Ø 18, L 35 mm

LED short



white L400069A

silver L400069S

LED long

white L400079A

silver L400079S




optional:
with cord switch



For technical data
see provita.de






innovative
& individual



Series 5



Our largest examination lamp

Highest light quality,
exactly where needed.



LED Temperature monitored LED control

Light output ~ 80,000 Lux / 1,000 mm*

Light colour approx. 4,500 K

Luminous flux 840 lm

Colour rendering index RA 94

Dimming levels 50 % / 65 % / 85 % /
100 %

Keypad with dimmer switch and control light

Adjustable light intensity through a
four-stage dimming function



Series 5
Large examination lamp



+ compact,
maintenance-free,
central lighting unit

+ shadow and
glare-free in the
working area

+ easily removable,
sterilisable handle

+ flexible
positioning
& true to position

Version without dimmer

approx. 60,000 Lux / 720 lm





MOBILE EXAMINATION LAMP
Flexible use at any time

Pivoting radius approx. 950 mm

Height adjustment approx. 1,000 mm

Total weight approx. 18.0 kg

With dimmer L511120A

With UPS L511125A

Without dimmer L511130A



WALL MOUNTED EXAMINATION LAMP
True to position through cardanic

Pivoting radius approx. 1,750 mm

Height adjustment approx. 1,000 mm

Total weight approx. 19.0 kg

With dimmer L540066A

Without dimmer L540076A

Optional: with UPS
(uninterrupted power supply)



+ High-Light-quality, temperature-monitored "OSRAM LEDs" generate the primary light with very high colour rendering, long service life and consistent light quality.

+ Flexible positioning due to true position cardan suspension with integrated weight compensation.

Series 5
Large examination lamp



**CEILING MOUNTED
EXAMINATION LAMP**
Comfortable controllable

Pivoting radius approx. 1,750 mm

Height adjustment approx. 1,000 mm

Total weight approx. 19.0 kg / 21.0 kg / 23.0 kg / 25.0 kg

For 2.5 m room height

With dimmer L525067A

Without dimmer L525077A

For 2.7 m room height

With dimmer L527067A

Without dimmer L527077A

For 3.0 m room height

With dimmer L530067A

Without dimmer L530077A

For 3.3 m room height

With dimmer L533067A


Without dimmer L533077A




The type of the ceiling lamp fastening must be determined by the customer. To clarify all technical details we would like to ask you to provide us with a sectional sketch of the room in the event of a project.

Our product consultants and technicians will be glad to assist you.

s. Substructure on p.13

 **+49 (0) 21 93 / 51 05 - 0**



optional:
with ceiling mounting plate

Cover for ceiling lamp




Please order cover separately
(Item no. Z2K0689A)



For technical data
see provita.de

Series 6



The outstanding reading lamp

Smart design
with a strong reading light.



LED
Optimized thermal management
and professional scattering optics

Light output 1,400 Lux/500 mm

Light colour 6,000 K

Luminous flux 53 lm

Electrical mains AC 100 – 240 V, 50 – 60 Hz



reddot award
honourable mention

Series 6
Reading lamp



+ highly flexible
protective hose
guarantees very good
hygienic properties

+ high quality
LED bulb
"high power"
from OSRAM



+ head made of
Stainless steel and
high-quality plastic



Made in
Germany

Upon request: international plug / 110 V version / connection to bed control /
operation through power control.
Many mounting options and further accessories starting on page 36.



GOOSENECK ARM LAMP

Decent and flexible reading lamp

Lamp head angle of rotation 315°

Tab diameter 18 mm

Gooseneck arm long > A

White L600035A

Silver L600035S

Gooseneck arm short > B

White L600025A

Silver L600025S

Gooseneck arm angled > C

White L620025A

Silver L620025S

The lamp can be operated with any common available battery if the battery meets the following requirements:

- USB connection
- 5V direct current
- min. 550 mA
- CE

With USB network adapter



Changeable power supply adapter unit

Europe 272786

Australia 274234

UK 274243

USA / Japan 274252

China 274261

Standard version: European plug (272786).
If a different changeable adapter is required, please specify country or plug type.



For technical data
see provita.de

Series 6
Reading lamp



Series 1 - 6

The right accessories

Everything you need
for installation.



**HEIGHT
ADJUSTABLE STAND**
Flexible on
a castor base

Colour white and chrome-plated steel

Tube diameter 25/18 mm

Height adjustment Single-handed system

Regulating range 1,080 mm – 1,745 mm

Base diameter approx. 635 mm

S011820A



FIXED HEIGHT STAND
Versatile and
stable

Colour white

Tube diameter 25 mm

Fixture entry Ø 18 mm

Base diameter approx. 635 mm

S000803A



**TUBE
MOUNTING BRACKET**
For fastening lamps
to tubes, Ø 25 – 50 mm

Material Aluminium

Bracket Ø 18 mm

Weight approx. 0.13 kg

White Z2N0502A

Silver Z2N0502S



OVAL-SHAPED WALL BRACKET

Low-noise rotation due to integrated plastic slide bush

Material Aluminium, white coated

Bracket Ø 18 mm

Size 55 × 156 mm

Distance between wall and fixture pin entry 120 mm

With threaded pin Z2N0619A



TABLE CLAMP WITH QUICK HAND FASTENER

For quick and easy attaching of lamps on table tops

Material Aluminium

Bracket Ø 18 mm

Clamping range 15 – 32 mm

Z2N0646S



COVER

Elegant cover for ceiling mounted lamps and possible ceiling gaps

Colour white

Diameter 320 mm

Height 70 mm

Weight approx. 0.5 kg

For ceiling lamps series 1 Z2K0679A

For ceiling lamps series 5 Z2K0689A



RAIL CLAMP

To attach lamps to 25 × 10 mm to 30 × 10 mm rails

Material Aluminium, ball-polished

Fixture entry Ø 18 mm

Weight approx. 0.2 kg

With threaded pin Z2N0643W



WALL MOUNTING BRACKET

For direct wall fastening of lamps, with 4 mounting holes

Material Aluminium, white coated

Fixture entry Ø 18 mm

Weight approx. 0.2 kg

With threaded pin Z2N0617A



For technical data
see provita.de

You have further questions?

**We will be glad
to help you personally.**

**Just give us a quick ring:
+49 (0) 21 93 / 51 05 - 0**

**Or e-mail us:
info@provita.de**

**For more than 50 years, our family
business has been one of the leading
manufacturers in medical technology.**



personal





experienced

motivated

Our general terms and conditions apply. Errors, misprints and changes reserved.

© Copyright: provita medical gmbh & co. kg, October 2019

Reproduction as well as duplication, also in extracts, are not permitted without permission of provita medical.



**Auf der Huhfuhr 8
42929 Wermelskirchen
Germany**

**Phone +49 (0) 21 93 / 51 05 - 0
Fax +49 (0) 21 93 / 51 05 - 269**

**info@provita.de
www.provita.de**

